

FlexScan EV2460

23.8" (60.5 cm) LCD Monitor



Small Footprint, Large Work Space

High Resolution in a Space-Saving Design

The EV2460 uses a 23.8-inch IPS panel with full HD (1920 x 1080) resolution. The small-footprint monitor has a width of just 537.8 mm for saving desk space. Furthermore, 140 mm height adjustment allows you to easily place a laptop under the monitor to realize a convenient dual-screen environment.

Low Impact on the Environment

The EV2460 implements EIZO's proprietary EcoView technologies, which cut power consumption by as much as 40% compared to displaying at maximum brightness and help to eliminate eyestrain when viewing the monitor for long periods.

- Adjusts screen brightness according to ambient lighting
- Adjusts backlight brightness and gain when displaying dark content

As part of its efforts to maintain environmentally responsible manufacturing, EIZO developed the monitor without flame retardant in the plastic body to improve recyclability and uses recyclable packing for the boxes the monitor is shipped in.

Rest Assured with Major Sustainability Standards

The monitor is certified by major comprehensive sustainability standards such as TCO Certified Generation 8, EPEAT, and EnergyStar. Organizations concerned with ESG investments or SDGs can assuredly procure the monitor to meet required guidelines.















FlexScan EV2460

Refreshing White with Frameless Design

The EV2460 comes with a white cabinet option with matching cables. Compared to black, white monitors offer a refreshing change that brightens the office with style. The frameless design further sophisticates the look.



The Perfect Position

The stand features wide range height adjustment, tilt, and swivel, while saving space and remaining stylish. You can adjust your monitor to the perfect position with ease.



Take Your Settings with You

EIZO's Screen InStyle proprietary software's Color Briefcase allows you to effortlessly maintain your individual screen preferences and take them with you, even to different monitors. Your settings are automatically reflected simply by connecting your laptop to a monitor supported by Screen InStyle. This is useful in environments with hot-desking or shared workspaces, providing enhanced comfort and work efficiency.



Person A's Settings

Person B's Settings

Say Goodbye to Tired Eyes

The EV2460 is equipped with functions to prevent eye fatigue even over long periods of use. With reduced eye fatigue,

concentration increases, leading to improved productivity.

- Auto brightness control
- 80% blue light reduction
- Anti-glare screen
- Flicker-free screen

paper such See the control of the c

Free Up Your Workspace with a Stand Bracket

The PCSK-03R is an optional VESA-compliant bracket for easily mounting a mini PC to the back of the monitor's stand to save work space on your desk.


Specifications

	орос.			
Stand	Model Variations		black / white	EV2460-BK / EV2460-WT
Size			black / white	EV2460-FBK / EV2460-FWT
Native Resolution	Panel		Type / Backlight	IPS / LED
Viewable Image Size (H x V) 527 x 296.5 mm Pixel Pitch / Pixel Density 0.275 x 0.275 mm / 93 ppi 0.275 x 0.2			Size	23.8" / 60.5 cm
Viewable Image Size (H x V) 527 x 296.5 mm			Native Resolution	1920 x 1080 (16: 9 aspect ratio)
Pixel Pitch / Pixel Density Display Colors 16.77 million			Viewable Image Size (H x V)	
Display Colors 16.77 million 178° / 178° 17				0.275 x 0.275 mm / 93 ppi
Viewing Angles (H / V, typical)				
Brightness (typical)				
Contrast Ratio (typical)				
Response Time (typical) 5 ms (gray-to-gray)				
Input Terminals DisplayPort (HDCP 1.3), HDMI (HDCP 1.4), DVI-D (HDCP 1.4), D-Sub mini 15 pin				
Digital Scanning Frequency (H/DCP 1.4), D-Sub mini 15 pin	Vidoo Signala			10 7 0 77
HOML 15 - 68 kHz / 49 - 51, 59 - 61 Hz	video Signais		<u>'</u>	(HDCP 1.4), D-Sub mini 15 pin
Color mode (User1, User2, SRGB, Paper, Movie, DICOM)				HDMI: 15 - 68 kHz / 49 - 51, 59 - 61 Hz
Upstream			(H/V)	
Downstream				
Audio Speakers 1.0 W + 1.0 W	USB			
Input Terminals Output Terminals Output Terminals Output Terminals Headphones (Stereo mini jack) Power Requirements AC 100 - 240 V, 50 / 60 Hz Typical Power Consumption Maximum Power Consumption Power Save Mode O.5 W or less Features & Functions Freatures & Color mode (User1, User2, sRGB, Paper, Movie, DICOM) Auto EcoView OSD Languages English, French, German, Italian, Japanese, Simplified and Traditional Chinese, Spanish, Swedish Dimensions (Landscape, W H x D) Dimensions (Portrait, W x H x D) Dimensions (Portrait, W x H x D) Net Weight Height Adjustment Range Tilt / Swivel / Pivot Environmental Requirements Operating Humidity (R.H., non condensing) Certifications & Standards (Please contact EIZO for the latest information.) Free Requirements In Question Set Terminals AC 100 - 240 V, 50 / 60 Hz Headphones (Stereo mini jack) AC 100 - 240 V, 50 / 60 Hz In W W H x D DW W I S D W So W I S D W			Downstream	71
Output Terminals	Audio		Speakers	1.0 W + 1.0 W
Power Requirements Typical Power Consumption Maximum Power Consumption Power Save Mode Power Save Mode Preset Modes Preset Modes Color mode (User1, User2, sRGB, Paper, Movie, DICOM) Auto EcoView Pos Danguages Physical Specifications Dimensions (Landscape, Wx H x D) Dimensions (Portrait, Wx H x D) Dimensions (Portrait, Wx H x D) Dimensions (Without Stand, Wx H x D) Net Weight Height Adjustment Range Titl / Swivel / Pivot Titl / Swivel / Pivot Environmental Requirements Poperating Humidity (R.H., non condensing) Certifications & Standards (Please contact EIZO for the latest information.) Power Save Mode O.5 W or less Color mode (User1, User2, sRGB, Paper, Movie, DICOM) So W So Danguages So W So W So W So Danguages So W So So W So So W So Danguages So W So			Input Terminals	Stereo mini jack, DisplayPort, HDMI
Typical Power Consumption Maximum Power Consumption Power Save Mode Preset Modes Color mode (User1, User2, sRGB, Paper, Movie, DICOM) Auto EcoView OSD Languages English, French, German, Italian, Japanese, Simplified and Traditional Chinese, Spanish, Swedish Physical Specifications Dimensions (Landscape, W x H x D) Dimensions (Portrait, W x H x D) Dimensions (Without Stand, W x H x D) Net Weight Height Adjustment Range Tilt / Swivel / Pivot So Up, 5° Down / 344° / 90° (both clockwise and counter clockwise) Hole Spacing (VESA Standard) Environmental Requirements Operating Temperature Operating Humidity (R.H., non condensing) Certifications & Standards (Please contact EIZO for the latest information.) Tilc Si V Up, 5° Down / 344° / 90° (both clockwise and counter clockwise) TCO Certified Generation 8, EPEAT 2018 (US), TÜV/Ergonomics, TÜV/Low blue light content, TÜV/Flicker Free, TÜV/GS, RCM, CE, CB, cTÜV/us, FCC-B, CAN (CSS-3, B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, EAC			Output Terminals	Headphones (Stereo mini jack)
Maximum Power Consumption 50 W	Power		Power Requirements	AC 100 - 240 V, 50 / 60 Hz
Power Save Mode Preset Modes Color mode (User1, User2, sRGB, Paper, Movie, DICOM) Auto EcoView SD Languages English, French, German, Italian, Japanese, Simplified and Traditional Chinese, Spanish, Swedish 537.8 x 333.6 - 473.6 x 233 mm Physical Specifications Dimensions (Landscape, W x H x D) Dimensions (Portrait, W x H x D) Dimensions (Without Stand, W x H x D) Net Weight Height Adjustment Range Tilt / Swivel / Pivot S57.8 x 320.4 x 550.3 - 588.9 x 233 mm 537.8 x 320.4 x 550.3 - 588.9 x 233 mm Tilt / Swivel / Pivot S57.8 x 320.4 x 550.3 - 588.9 x 233 mm 537.8 x 320.4 x 550.3 - 588.9 x 233 mm Tilt / Swivel / Pivot S57.8 x 320.4 x 550.3 - 588.9 x 233 mm 537.8 x 320.4 x 550.3 - 588.9 x 233 mm Tolor mode (User1, User2, sRGB, Paper, Movie, DICOM) S57.8 x 333.6 - 473.6 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm Tolor mode (User1, User2, sRGB, Paper, Movie, DICOM) S57.8 x 333.6 - 473.6 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm Tolor mode (User1, User2, sRGB, Paper, Movie, DICOM) S57.8 x 333.6 - 473.6 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 588.9 x 233 mm S57.8 x 320.4 x 550.3 - 589.9 x 233 mm S57.8 x 320.4 x 550.3 - 589.9 x 233 mm S57.8 x 320.4 x 550.3 - 589.9 x 233 mm S57.8 x 320.4 x 550.3 - 589.9 x 233 mm S57.8 x 320.4 x 550.3 - 589.9 x 233 mm S57.8 x 320.4 x 550.3 - 589.9 x 233 mm S57.8 x 320.4 x 550.3 - 589.9 x 233 mm S57.8 x 320.4 x 550.3 - 589.9 x 233 mm S57.8 x 320.4 x 550.3 - 589			Typical Power Consumption	10 W
Features & Functions Preset Modes Auto EcoView OSD Languages English, French, German, Italian, Japanese, Simplified and Traditional Chinese, Spanish, Swedish Specifications Dimensions (Landscape, W x H x D) Dimensions (Portrait, W x H x D) Dimensions (Without Stand, W x H x D) Net Weight Height Adjustment Range Tilt / Swivel / Pivot Environmental Requirements Operating Temperature Operating Humidity (R.H., non condensing) Certifications & Standards (Please contact EIZO for the latest information.) Preset Modes Color mode (User1, User2, sRGB, Paper, Movie, DICOM) 100 Mode (User1, User2, sRGB, Paper, Movie, DICOM) 20.4 x 550.3 - 588.9 x 233 mm 320.4 x 550.3 - 588.9 x 233 mm 320.4 x 550.3 - 588.9 x 233 mm 40 mm 537.8 x 320.4 x 53.6 mm 40 mm 100 mm 100 x 100 mm 5 - 35 °C 20 - 80 % Cortifications & Standards (Please contact EIZO for the latest information.) TCO Certified Generation 8, EPEAT 2018 (US), TÜV/Erge, TÜV/S, RGM, CE, CB, ED, TÜV/S, RGM, CE, CB, TÜV/S, SCO-B, CPA, EN, CES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, EAC			Maximum Power Consumption	50 W
Functions Auto EcoView OSD Languages English, French, German, Italian, Japanese, Simplified and Traditional Chinese, Spanish, Swedish Specifications Dimensions (Landscape, W x H x D) Dimensions (Portrait, W x H x D) Dimensions (Without Stand, W x H x D) Net Weight Height Adjustment Range Tilt / Swivel / Pivot Tilt / Swivel / Pivot Sor Up, 5° Down / 344° / 90° (both clockwise and counter clockwise) Hole Spacing (VESA Standard) Poperating Temperature Operating Humidity (R.H., non condensing) Certifications & Standards (Please contact EIZO for the latest information.) DIMENSION (Please Contact EIZO for the latest information.) DIMENSION (Please Contact EIZO for the latest information.)			Power Save Mode	0.5 W or less
Dimensions (Landscape, Wx H x D) Dimensions (Portrait, Wx H x D) Dimensions (Without Stand, Wx H x D) Dimensions (Without Stand	Features & Functions		Preset Modes	
Dimensions (Landscape, Wx H x D) Dimensions (Portrait, Wx H x D) Dimensions (Portrait, Wx H x D) Dimensions (Without Stand, Wx			Auto EcoView	Yes
W x H x D) Dimensions (Portrait, W x H x D) Dimensions (Portrait, W x H x D)			OSD Languages	English, French, German, Italian, Japanese, Simplified and Traditional Chinese, Spanish, Swedish
W x H x D Dimensions (Without Stand, W x H x D) S37.8 x 320.4 x 53.6 mm W x H x D S4 x M x D S57.8 x 320.4 x 53.6 mm W x H x D Net Weight S.9 kg / 3.8 kg (Without Stand) Height Adjustment Range 140 mm Tilt / Swivel / Pivot 35° Up, 5° Down / 344° / 90° (both clockwise and counter clockwise) Hole Spacing (VESA Standard) 100 x 100 mm Deprating Temperature 5 - 35 ° C Operating Humidity (R.H., non condensing) 20 - 80 % Certifications & Standards TCO Certified Generation 8, EPEAT 2018 (US), TÜV/ Ergonomics, TÜV/Low blue light content, TÜV/Flicker Free, TÜV/GS, RCM, CE, CB, CID/Uss, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, EAC	Physical Specifications			537.8 x 333.6 - 473.6 x 233 mm
W x H x D) Net Weight 5.9 kg / 3.8 kg (Without Stand) Height Adjustment Range 140 mm Tilt / Swivel / Pivot 35° Up, 5° Down / 344° / 90° (both clockwise and counter clockwise) Hole Spacing (VESA Standard) 100 x 100 mm Doperating Temperature 5 - 35 °C Operating Humidity (R.H., non condensing) Certifications & Standards Please contact EIZO for the latest information.) TCO Certified Generation 8, EPEAT 2018 (US), TÜV/Ergonomics, TÜV/Low blue light content, TÜV/Ficker Free, TÜV/GS, RCM, CE, CB, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, EAC			Dimensions (Portrait, W x H x D)	320.4 x 550.3 - 588.9 x 233 mm
Height Adjustment Range 140 mm 35° Up, 5° Down / 344° / 90° (both clockwise and counter clockwise) Hole Spacing (VESA Standard) 100 x 100 mm				537.8 x 320.4 x 53.6 mm
Till / Swivel / Pivot 35° Up, 5° Down / 344° / 90° (both clockwise and counter clockwise) Hole Spacing (VESA Standard) 100 x 100 mm Environmental Requirements Operating Temperature 5 - 35 ° C Operating Humidity (R.H., non condensing) Certifications & Standards (Please contact EIZO for the latest information.) TCO Certified Generation 8, EPEAT 2018 (US), TÜV/ Ergonomics, TÜV/Low blue light content, TÜV/Flicker Free, TÜV/GS, RCM, CE, CB, CTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, EAC			Net Weight	5.9 kg / 3.8 kg (Without Stand)
Counter clockwise			Height Adjustment Range	140 mm
Derating Temperature Departing Temperature Departing Humidity (R.H., non condensing) 20 - 80 %			Tilt / Swivel / Pivot	
Operating Humidity (R.H., non condensing) 20 - 80 %			Hole Spacing (VESA Standard)	100 x 100 mm
Certifications & Standards (Please contact EIZO for the latest information.) TCO Certified Generation 8, EPEAT 2018 (US), TÜV/Ficker Free, TÜV/GS, RCM, CE, CB, CTÜV/us, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, EAC	Environmental Requirements		Operating Temperature	5 - 35 °C
(Please contact EIZO for the latest information.) Ergonomics, TÜV/I.Cw blue light content, TÜV/Flicker Free, TÜV/GS, RCM, CE, CB, cTUVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, EAC				20 - 80 %
Dedicated Monitor Control Utility Screen InStyle Supported	Certifications & Standards (Please contact EIZO for the latest information.)			Ergonomics, TÜV/Low blue light content, TÜV/Flicker Free, TÜV/GS, RCM, CE, CB, CTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star,
	Dedicated Software	dt	Monitor Control Utility	Screen InStyle Supported
	Supplied Accessories (May vary by country. Please contact EIZO for details.)		Signal Cables	DisplayPort (2 m)
May vary by country. Please contact EIZO WESA mount x4, setup guide			Others	
	Warranty			Five Years *

*Usage time is limited to 30,000 hours. Free from bright sub-pixels for 6 months from the date of purchase. With current LCD technology, a panel may contain a limited number of missing or

with current ECD technology, a panet may contain a timited number of missing or flickering pixels. If the monitor is left on continuously over a long period of time, dark smudges or burn-in may appear. To maximize the life of the monitor, we recommend the monitor be turned off periodically.

Dimensions (Unit: mm)



EIZ Corporation

153 Shimokashiwano, Hakusan, Ishikawa 924-8566 Japan Phone: +81-76-277-6794 Fax:+81-76-277-6793 www.eizoglobal.com All product names are trademarks or registered trademarks of their respective companies. EIZO, the EIZO logo, and FlexScan are registered trademarks of EIZO Corporation in Japan and other countries. Screen InStyle is a trademark of EIZO Corporation. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and other countries. DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information, VESA is a registered trademark of Video Electronics Standards Association. ENERGY STAR is a registered trademark of the United States and other countries. Some screen images are used with permission from Microsoft. Specifications are subject to change without notice.