



MultiEdge Series

**15", 16" & 17" THIN BEZEL LCD MONITORS
WITH INTEGRATED SPEAKERS**

*Quality
on Display*

The Compact Way To Higher Performance

The MultiEdge Series offers corporate and administrative users a selection of LCD monitors that integrate all the key advantages of EIZO's display technology in a choice of practical screen sizes.

Primary benefits include a thin bezel design that saves space on the desktop, built-in stereo speakers for multimedia capability, and digital/analog connectors. Accurate color control and wide-ranging adjustment of brightness and contrast make it easy to fine-tune the image as required for the application in use. On performance alone, these monitors are convincing replacements for 17" and 19" CRTs, quite apart from the obvious benefit of their compact size. Flexible placement options and the thin bezel profile also make them ideal for multi-panel tiling.


Available in three sizes — 15", 16" and 17" — the MultiEdge Series gives an impressive look to the desktop while delivering the performance quality, space efficiency and greater productivity sought by today's professional users.

THE MULTI-PANEL ADVANTAGE

The compact design of the MultiEdge Series is ideal for multi-display systems, because it puts more viewing area into less workspace and provides near-seamless viewing between monitors. Enabling several open applications to be seen simultaneously, such systems are increasingly recognized as an effective means to greater productivity. Users can handle more programs, compare more information, and track more data, without constant task-switching between windows. In almost any professional work environment, that saves space and time while making work much easier.

DIGITAL AND ANALOG INPUT

Inclusion of both DVI-D and D-Sub 15-pin connectors allows the monitors to be used with a computer incorporating either a digital or an analog graphics card — or both, if two computers are connected at the same time. The user can alternate between the two connectors via a button on the front bezel.



INTEGRATED SPEAKERS

Space-efficient and multimedia ready, these monitors feature built-in stereo speakers with volume and mute controls and an external headphone jack.



ADVANCED COLOR CONTROL

MultiEdge monitors offer an expanded color space on par with that established by the European Broadcasting Union. The ColorManagement function, pioneered by EIZO, takes advantage of this expansion to give the user independent adjustment and control of hue, gain, saturation and color temperature.

sRGB MODE

Compatibility with the international sRGB color space enables color matching with applications and peripherals like scanners, printers and digital cameras. This ensures color consistency in daily office tasks as well as in online shopping, since sRGB is also the default color space for the Web.

IMAGE CLARITY

Wide viewing angles make sure that the on-screen image remains bright and clear, with consistent color levels, even when seen from an oblique position. Contrast and brightness settings are among the highest in their respective classes, producing more distinct images with sharper detail.

AUTO ADJUSTMENT

This feature automatically centers the displayed image via a one-touch button on the front panel.

FREE MOUNT CAPABILITY

Compliance with VESA mounting standards affords the user the option of mounting on the wall or an adjustable arm. Panel-integrated power supply units make installation easy, since there is no separate power brick or cord.




LOW POWER CONSUMPTION

All models consume less than half the power required by a CRT of comparable viewing size. Power saving functions reduce consumption to less than 3 watts in standby mode.



MODEL IDENTIFICATION

The ScreenManager® on-screen display menu shows the model name, serial number, and total usage hours.



SAFETY LOCK SUPPORT



All models include a slot for connection of a security cable (sold separately). The slot supports Kensington's Microsaver® security system.

INTERNATIONAL STANDARDS

The MultiEdge Series satisfies a wide range of current industry standards relating to low emissions, ergonomics, recycling, safe usage and power management. These include TCO'99, TÜV/Ergonomics, the CE Mark, Energy 2000, and the EPA Energy Star® Program.



PROTECTION SHEETS

Optional high-transparency sheets, available in three sizes to match each model, protect the screen surface from dust and scratches.

MultiEdge Series

THIN BEZEL LCD MONITORS WITH INTEGRATED SPEAKERS



FlexScan® L565



FlexScan® L465



FlexScan® L365

<i>Panel Size and Type</i>	43 cm (17") TFT color LCD panel	41 cm (16") TFT color LCD panel	38 cm (15") TFT color LCD panel
<i>Available Cabinet Colors</i>	Gray, Black	Gray, Black	Gray, Black
<i>Pixel Pitch</i>	0.264 mm × 0.264 mm	0.248 mm × 0.248 mm	0.297 mm × 0.297 mm
<i>Display Colors</i>	16.7 million	16.7 million	16.7 million
<i>Viewing Angles</i>	H: 170°, V: 170°	H: 160°, V: 130°	H: 160°, V: 150°
<i>Scanning Frequency (H, V)</i>	Analog: 24.8 – 80 kHz, 50 – 75 Hz	Analog: 24.8 – 80 kHz, 50 – 75 Hz	Analog: 24 – 60 kHz, 55 – 75 Hz
	Digital: 31.5 – 64 kHz, 60 Hz (VGA Text: 70 Hz)	Digital: 31.5 – 64 kHz, 60 Hz (VGA Text: 70 Hz)	Digital: 31.5 – 48 kHz, 60 Hz (VGA Text: 70 Hz)
<i>Recommended Resolution</i>	1280 × 1024	1280 × 1024	1024 × 768
<i>Brightness</i>	230 cd/m ² (typical)	250 cd/m ² (typical)	300 cd/m ² (typical)
<i>Contrast Ratio</i>	400:1 (typical)	400:1 (typical)	450:1 (typical)
<i>Response Time</i>	40 ms (typical)	45 ms (typical)	25 ms (typical)
<i>Dot Clock</i>	Analog: 135 MHz, Digital: 108 MHz	Analog: 135 MHz, Digital: 108 MHz	Analog: 80 MHz, Digital: 65 MHz
<i>Input Signals</i>	RGB Analog, DVI Standard 1.0	RGB Analog, DVI Standard 1.0	RGB Analog, DVI Standard 1.0
<i>Input Terminals</i>	D-Sub mini 15 pin, DVI-D 24 pin (switchable)	D-Sub mini 15 pin, DVI-D 24 pin (switchable)	D-Sub mini 15 pin, DVI-D 24 pin (switchable)
<i>Active Display Size (H × V)</i>	338 mm × 270 mm	317 mm × 253 mm	304 mm × 228 mm
<i>Viewable Image Size</i>	432 mm (diagonal)	406 mm (diagonal)	380 mm (diagonal)
<i>Plug & Play</i>	VESA DDC 2B	VESA DDC 2B	VESA DDC 2B
<i>Screen Control</i>	ScreenManager®,	ScreenManager®,	ScreenManager®,
	One Touch Auto Adjustment Function	One Touch Auto Adjustment Function	One Touch Auto Adjustment Function
<i>Power Requirements</i>	AC 100 -120V/200-240V, 50-60 Hz	AC 100 -120V/ 200-240V, 50-60 Hz	AC 100 -120V/ 200-240V, 50-60 Hz
<i>Power Management</i>	VESA DPMS, DVI-DMPM	VESA DPMS, DVI-DMPM	VESA DPMS, DVI-DMPM
<i>Power Consumption</i>	45 watts (typical)	45 watts (typical)	35 watts (typical)
<i>Power Save Mode</i>	Less than 3 watts	Less than 3 watts	Less than 3 watts
<i>OSD Languages</i>	English, French, German, Italian, Spanish, Swedish	English, French, German, Italian, Spanish, Swedish	English, French, German, Italian, Spanish, Swedish
<i>Dimensions (W × H × D)</i>	With Stand: 380 mm × 416 mm × 178 mm	With Stand: 370 mm × 398 mm × 157 mm	With Stand: 340 mm × 369 mm × 157 mm
	Without Stand: 380 mm × 353 mm × 58 mm	Without Stand: 370 mm × 333 mm × 54 mm	Without Stand: 340 mm × 301 mm × 48 mm
<i>Net Weight</i>	With Stand: 5.8 kg, Without Stand: 4.5 kg	With Stand: 5.0 kg, Without Stand: 4.0 kg	With Stand: 4.1 kg, Without Stand: 3.2 kg
<i>Audio</i>	Dual 1-watt built-in speakers, input/headphone jacks	Dual 1-watt built-in speakers, input/headphone jacks	Dual 1-watt built-in speakers, input/headphone jacks
<i>Tilt</i>	30° Up, 3° Down	30° Up, 3° Down	30° Up, 3° Down
<i>Certifications and Standards</i>	TCO'99 ¹ , TÜV/Ergonomics, TÜV/GS,	TCO'99 ¹ , TÜV/Ergonomics, TÜV/GS,	TCO'99 ¹ , TÜV/Ergonomics, TÜV/GS,
	c-Tick, CE, CB, UL 1950,	c-Tick, CE, CB, UL 1950,	c-Tick, CE, CB, UL 1950,
	CSA C22.2 No.950, FCC-B,	CSA C22.2 No.950, FCC-B,	CSA C22.2 No.950, FCC-B,
	Canadian ICES-003-B, TÜV/S, VCCI-B,	Canadian ICES-003-B, TÜV/S, VCCI-B,	Canadian ICES-003-B, TÜV/S, VCCI-B,
<i>Supplied Accessories</i>	EPA ENERGY STAR®, Energy 2000	EPA ENERGY STAR®, Energy 2000	EPA ENERGY STAR®, Energy 2000
	AC power cord, user's manual, signal cable	AC power cord, user's manual, signal cable	AC power cord, user's manual, signal cable
	(D-Sub mini 15 pin), audio cable, 4 screws	(D-Sub mini 15 pin), audio cable, 4 screws	(D-Sub mini 15 pin), audio cable, 4 screws
	for mount option, warranty registration card	for mount option, warranty registration card	for mount option, warranty registration card

¹ Gray cabinet only.

With current LCD technology, a panel may contain a limited number of missing or flickering pixels.

Specifications are subject to change without notice.

ENERGY STAR is a U.S. registered mark. As an ENERGY STAR® Partner, Eizo Nanao Corporation has determined that the products specified herein meet the ENERGY STAR® guidelines for energy efficiency.

Published on chlorine-free paper.
Copyright© 2002 Eizo Nanao Corporation. All rights reserved. All product names are trademarks or registered trademarks of their respective companies. EIZO, FlexScan, and ScreenManager are registered trademarks of Eizo Nanao Corporation.

(020202) Printed in Japan, 2,2002, 6K

EIZO NANAO CORPORATION

153 Shimokashiwano, Matto, Ishikawa 924-8566 Japan

Phone: +81-76-277-6792 Fax: +81-76-277-6793

www.eizo.com

